






深圳市永连旺电子有限公司

Shenzhen Yonglianwang Electronic CO., LTD.

1.00mm Pin Header, Dual Row, S. M. T

SPECIFICATIONS

Current Rating : 0.75AMP
 Operation Temperature: -40° C to +105° C
 Contact Resistance : 30mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage : AC 500V
 Insulator Material : High Temperature
 Thermoplastic (UL94V-0)
 Contact Material : Phosphor Bronze
 Contact plating : Au over 50 u" Ni



PCB LAYOUT

Ordering Information

1 5 10 — 1	2 XX	G0	M XXX 01
Plastics Height 10=1.0mm 15=1.5mm	No. of Pins Per Row 01~ 50	Contact Plating SN : Tin G0 : Gold Flash G2 : 5u" Gold G3 : 10u" Gold G4 : 15u" Gold G5 : 30u" Gold S0 : Gold Flash/Tin Standard: G0	Pin Length XXX=B+H+D+ (W-1.0) / 2

Tel : 86-0755-27367782

Fax : 86-0755-27382610

Http://www.szyLconn.com

E-mail:sales@szyLconn.com

地址:广东省深圳市宝安区福永街道兴围第一工业区兴华路北第17幢