




# 深圳市永连旺电子有限公司

## Shenzhen Yonglianwang Electronic CO., LTD.



### 1. 27mm Board Spacer, Dual Row, S. M. T

#### SPECIFICATIONS

Current Rating : 1AMP  
 Operation Temperature: -40° C to +105° C  
 Contact Resistance : 20mΩ Max.  
 Insulation Resistance: 1000MΩ Min.  
 Withstanding Voltage : AC 500V  
 Insulator Material : Polyester (UL94V-0)  
 Standard: Nylon-6T  
 Contact Material : Brass  
 Contact plating : Au or Sn Over 50u" Ni



PCB LAYOUT



#### Ordering Information

1 3 15 — 2	2 XX	G0	M XXX 01
Plastics Height 10=1.0mm 15=1.5mm	No. of Pins Per Row 01~50	Contact Plating SN : Tin G0 : Gold Flash G2 : 5u" Gold G3 : 10u" Gold G4 : 15u" Gold G5 : 30u" Gold S0 : Gold Flash/Tin Standard: G0	Pin Length XXX=B+C+D+(W-1.27)/2

Tel : 86-0755-27367782

Fax : 86-0755-27382610

Http://www.szyLconn.com

E-mail:sales@szyLconn.com

地址:广东省深圳市宝安区福永街道兴围第一工业区兴华路北第17幢