



深圳市永连旺电子有限公司

Shenzhen Yonglianwang Electronic CO.,LTD.

2.00mm Female Header, Single Row, S. M. T

SPECIFICATIONS

Current Rating : 1.5AMP
 Operation Temperature: -40° C to +105° C
 Contact Resistance : 20mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage : AC 500V
 Insulator Material : Polyester (UL94V-0)
 Standard: Nylon-6T
 Contact Material : Phosphor Bronze
 Contact plating : Au over 50 u² Ni



PCB LAYOUT

Ordering Information

2 2 43 — 1	XX	M	G0	B U N 01
Plastics Height	No. of Pins Per Row	Contact Plating	Material Type	
40=4.0mm 43=4.3mm 46=4.6mm	03~50	SN : Tin G0 : Gold Flash G2 : 5u ² Gold G3 : 10u ² Gold G4 : 15u ² Gold G5 : 30u ² Gold S0 : Gold Flash/Tin Standard: G0	B: Nylon-66 C: Nylon-6T D: LCP	

Tel : 86-0755-27367782

Fax : 86-0755-27382610

Http://www.szyLconn.com

E-mail:sales@szyLconn.com

地址:广东省深圳市宝安区福永街道兴围第一工业区兴华路北第17幢